



FEATURES

- Designed for supply slurry transfer, water transfer, and produced water applications
- Synthetic woven liner reinforcement designed for high pressure pumping
- Resistant to ozone and abrasion
- Through-the-weave extrusion and normalized for consistent sizing

- Lengths available to 660'
- Oversized ID design to fit most couplings
- Diameters: 4", 6", 8", 10" & 12"
- Color: black
**Other colors available with MOQ*
- Exclusive snake resistant technology
- Designed for 10 years of service life or water transfer of 5 billion gallons of water

Meets All the Requirements of NFPA 1961 (1960) Standard on Fire Hose

POLYEX HP

THROUGH-THE-WEAVE POLYURETHANE TRANSFER HOSE

HOSE SIZE AND SPECIFICATIONS

INSIDE DIAMETER	THICKNESS	WEIGHT/FT. COUPLED	WORKING PRESSURE	TEST PRESSURE	BURST PRESSURE
INCHES	INCHES	POUNDS	PSI	PSI	PSI
4"	.12"	1.0 lbs	250 psi	500 psi	750 psi
6"	.14"	1.4 lbs	250 psi	500 psi	750 psi
8"	.15"	2.3 lbs	250 psi	500 psi	750 psi
10"	.16"	3.3 lbs	210 psi	420 psi	750 psi
12"	.18"	4.0 lbs	175 psi	350 psi	525 psi