



MATEX
hose

FEATURES

- Reinforced with a stable tube capable of withstanding up to 300 psi (1½"), with a 3:1 safety factor offering burst pressures of 1000 psi.

- Durable cover resists wear, while low drag surfaces allow for easy handling.

- 1½" 250 psi hose is designed to meet UL 92 requirements.

- Color: Red

- 1½" diameter hoses are available in black or red on bulk reels.

- 800 PSI W/P for 1" HP feature 3:1 working pressure to burst pressure

- Completely kink resistant

Coast Guard: Meets US Coast Guard requirements.

Designed to pass MIL-SPEC MIL-H-24580 specifications.



RED ALARM BOOSTER

SYNTHETIC RUBBER 4 SPIRAL YARN NON-COLLAPSIBLE HARDWALL BOOSTER HOSE

HOSE SIZE AND SPECIFICATIONS

INSIDE DIAMETER	OUTSIDE DIAMETER	WEIGHT/FT. COUPLED	WORKING PRESSURE	TEST PRESSURE	BURST PRESSURE
INCHES	INCHES	POUNDS	PSI	PSI	PSI
3/4"	1.15"	.40 lbs	300 psi	600 psi	1000 psi
1"	1.5"	.58 lbs	300 psi	600 psi	1000 psi
1" HP	1.5"	.70 lbs	800 psi	1600 psi	2400 psi
1 1/2"	2.06"	.77 lbs	300 psi	600 psi	1000 psi